

## MULTI-FUNCTIONAL VALVE RADIATOR



### Connections

4 x internal thread G 1/2  
2 x G 3/4"



### Test positive pressure

13 bar



### Max. positive operating pressure

10 bar



### Max. operating temperature

110 °C

### Heat emission

The specification was verified in accordance with DIN EN 442 at The Technical University, Stuttgart (Registration at WSP-Cert Product Certification Centre, Stuttgart), under the numbers:

Type 11 KV	0445
Type 21 KV-S	0447
Type 22 KV	0448
Type 33 KV	0449

and in accordance with OENORM (Austrian standard) EN 442 at the Technological Commercial Museum, Vienna.

### Material

MULTI-FUNCTIONAL VALVE RADIATORS are made of cold-rolled sheet

steel, in accordance with EN 442-1, with a stylish and robust fluting, with ribs at 40 mm intervals.

### Equipment

Each MULTI-FUNCTIONAL VALVE RADIATOR is equipped with an integrated valve set, and suitable for double-pipe and single-pipe systems with a single-pipe manifold; it comes with a fitted valve top with a pre-set  $k_v$ -value, a protective cap and welded suspension brackets on the back, (brackets only when defined as such); type 11 only available with brackets. The drain plug and the pivotable vent plug, as well as the dummy plug are fitted with seals. All radiators are equipped with a detachable top cover and two closed side panels.


### Paint coating

1. Undercoating in accordance with DIN 55900 part 1, stoved at 190° C.
2. Finish in accordance with DIN 55900 part 2, in standard colour 9016 (on request available in many standard colours and sanitary-ware colours at an extra charge), applied electrostatically in a modern powder coating facility. This especially resistant coating is stoved at an object temperature of 210° C.

### Packaging

1. Cardboard packaging
2. Edge protection
3. Shrink foil

Overview of models



Profile radiator

Type	11 KV					21 KV-S					22 KV					33 KV				
Height ↑↓ [mm]	300	400	500	600	900	300	400	500	600	900	300	400	500	600	900	300	400	500	600	900
Length ↔ [mm]	up to 2400		up to 2600		up to 2000	up to 2400		up to 3000		up to 2000	up to 3000		up to 2000		up to 3000	up to 2200		up to 2000		
Steps	any overall length starting with 400 mm available in steps of 200 mm, additionally 520, 720, 920, 1120 and 1320 mm																			

## 24 MULTI-FUNCTIONAL VALVE RADIATOR

### Description and delivery equipment

#### Description and delivery equipment

The MULTIFUNCTIONAL VALVE RADIATOR with its welded valve unit has been designed in a most trend-setting way: it can meet all requirements regarding connections.

This radiator will convince you not only because of its simple and fast installation but also because of its versatility and elegant appearance, as the valve unit is covered up by the heating panel.

What's more, through the optimal function of the whole radiator-valve unit, through the maximum heat output and, last but not least, through the motivation to install thermostat heads, saving heating energy becomes evident.

The MULTIFUNCTIONAL VALVE RADIATOR with its welded valve unit is suitable for double-pipe as well as for single-pipe installations, using a one-pipe manifold. Additionally to the connection possibility at the bottom, the sophisticated design also offers connection possibilities, known from compact radiators, such as single-sided or two-sided connections. **The radiator is delivered ready for double-pipe installation, with a factory-adjusted  $k_v$ -setting, appropriate to the radiator output.**

For district heating installations with a big difference between water supply and return temperature, a steplessly adjustable valve element is available on request.

By using universal supply and return connections with external thread 3/4", commercially available pipes made of copper, precision steel or plastic, can

be connected, using the corresponding accessories and the commercially obtainable shut-off valve.

The decor-clips (standard make in standard colour 9016) offer many possibilities for design. They are available in many standard and sanitary-ware colours, as well as with metallic surfaces, i.e. gilded.


The following thermostat heads can be installed directly onto the radiator: „RA 2000“ and „RAW“ by Danfoss, „VK“ by

Heimeier, „theraDA“ by MNG, as well as „UNI XD“ by Oventrop. At delivery the radiator is equipped with a protective cap.


The operation parameters are specified as follows: positive operating pressure 10 bar, operating temperature 110° C. With single-pipe installations a maximum heat output of about 10 kW at  $\Delta T = T_1 - T_2 = 20$  K (at  $T_1 = 90$  °C) per ring has to be taken into account.




Connection modes - double-pipe system




A:  
Single-sided  
connection



B:  
Connection  
both sides



C:  
Connection  
on top  
  
(Warning: Lower  
performance)




D:  
Single-sided  
connection

**Attention:**  
If the multifunctional valve radiator is used as compact radiator, the crew caps made of plastic have to be replaced by nickel-plated brass caps (accessory).  
Order number: AZ0PL000C0002000



Single-pipe operation - factory-adjusted built-in valve

Single-pipe operation - factory-adjusted built-in valve



In single-pipe operation, setting the built-in valve on N.

The radiator will be delivered with a protective cap. After removing the protective cap (item A) the following thermostat heads can be installed directly onto the built-in valve (item B): „RA 2000“ and „RAW“ by Danfoss, „VK“ by Heimeier, „theraDA“ by MNG, as well as „UNI XD“ by Oventrop.

Caution:

During the installation take care that the return element (2) has been installed at the water return, and the supply element (1) at the water supply.

Changing the built-in valve from the right- to the left-hand side can easily be done at any time.




Chart 2 pressure drop [mbar] - single-pipe operation with a proportional deviation of 2K.

Default setting:

- radiator proportion 30%: 3,50 revolutions \*
- radiator proportion 35%: 3,00 revolutions \*
- radiator proportion 40%: 2,50 revolutions \*
- radiator proportion 45%: 2,00 revolutions \*
- radiator proportion 50%: 1,75 revolutions \*

\*...when starting, turn the bypass spindle of the one-pipe manifold **to the right** as far as it will go..

Of course it is also possible to change the pre-adjusted valve setting when the equipment is operating at pressure.

Please take into account the maximum power per cycle (regarding single-pipe installations) of about 10 kW  $\Delta T = T_1 - T_2 = 20 \text{ K}$  (at  $T_1 = 90 \text{ }^\circ\text{C}$ ).

## 28 COMPACT RADIATOR

### Technical data

## COMPACT RADIATOR



**Connections**  
4 x internal thread G 1/2



**Test positive pressure**  
13 bar



**Max. positive operating pressure** 10 bar



**Max. operating temperature** 110 °C

### Heat emission

The specification was verified in accordance with DIN EN 442 at The Technical University, Stuttgart (Registration at WSP-Cert Product Certification Centre, Stuttgart), under the numbers:

Type 10	0443
Type 11 K	0445
Type 21 K-S	0447
Type 22 K	0448
Type 33 K	0449

and in accordance with OENORM (Austrian standard) EN 442 at the Technological Commercial Museum, Vienna.

### Material

COMPACT RADIATORS are made of cold-rolled sheet steel, and in accordance with EN 442-1, with a stylish and robust fluting, with ribs at 40 mm intervals.

### Equipment

Each COMPACT RADIATOR is equipped with wall brackets that are welded onto the back. The radiator types 11 K, 21 K-S, 22 K and 33 K are equipped with a detachable top cover and two closed side panels.


### Paint coating

1. Undercoating in accordance with DIN 55900 part 1, stoved at 190° C.
2. Finish in accordance with DIN 55900 part 2, in standard colour 9016 (on request available in many standard colours and sanitary-ware colours at an extra charge), applied electrostatically in a modern powder coating facility. This especially resistant coating is stoved at an object temperature of 210° C.

### Packaging

1. Cardboard packaging
2. Edge protection
3. Shrink foil

OVERVIEW OF MODELS




Profile radiator

Type	10					11 K					21 K-S					22 K					33 K				
Height ↑ ↓ [mm]	300	400	500	600	900	300	400	500	600	900	300	400	500	600	900	300	400	500	600	900	300	400	500	600	900
Length ↔ [mm]	up to 1200	up to 2400	up to 2600	up to 1400		up to 2400	up to 2600	up to 2000			up to 2400	up to 3000	up to 2000			up to 3000	up to 2000	up to 3000			up to 2200	up to 2000			
Steps	all overall length starting with 400 mm available in steps of 200 mm, additionally 520, 720, 920, 1120 and 1320 mm																								

## 30 COMPACT RADIATOR

### Connection modes - double-pipe and single-pipe system


#### Connection modes - double-pipe system



**A:**  
Single-sided connection




**B:**  
Connection both sides




**C:**  
Connection on top  
**(Warning: Lower performance)**

#### Connection modes - single-pipe system



COMPACT RADIATORS can easily be converted for a single-pipe connection, provided that four-way valves with a by-pass pipe are used.



360 ° views  
available at [www.vogelundnoot.com](http://www.vogelundnoot.com)

90/70/20° C		Side panels and top cover of COMPACT, T6- and MULTI-FUNCTIONAL VALVE RADIATORS are taken into consideration in the performance data																								
		Radiator power data in watts, in accordance with DIN EN 442 supply temperature 90 - return temperature 70 - room temperature 20° C																								
↑ ↓ Height [mm]	Type	300					400					500					600					900				
		10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM
← → Length [mm]	Power																									
400	Watt	176	288	427	558	796	224	362	534	695	992	271	430	625	787	1140	317	478	689	875	1251	446	659	949	1173	1649
520	Watt	228	374	555	725	1035	292	470	694	903	1289	353	559	812	1023	1482	412	621	896	1138	1626	579	856	1233	1524	2144
600	Watt	263	432	640	837	1194	337	543	801	1042	1488	407	645	937	1181	1710	475	717	1034	1313	1877	668	988	1423	1759	2474
720	Watt	316	518	769	1005	1433	404	651	961	1250	1785	488	774	1124	1417	2052	570	860	1241	1576	2252	802	1186	1707	2111	2969
800	Watt	351	576	854	1116	1592	449	723	1068	1389	1984	543	859	1249	1574	2280	634	955	1379	1751	2502	891	1318	1897	2345	3299
920	Watt	404	662	982	1284	1830	516	832	1229	1598	2281	624	988	1437	1810	2622	729	1099	1585	2013	2878	1025	1515	2182	2697	3793
1000	Watt	439	720	1067	1395	1990	561	904	1335	1737	2479	678	1074	1562	1968	2850	792	1194	1723	2188	3128	1114	1647	2371	2931	4123
1120	Watt	492	806	1195	1563	2228	628	1013	1496	1945	2777	760	1203	1749	2204	3192	887	1338	1930	2451	3503	1247	1845	2656	3283	4618
1200	Watt	527	864	1281	1674	2388	673	1085	1602	2084	2975	814	1289	1874	2361	3420	951	1433	2068	2626	3753	1337	1977	2846	3518	4948
1320	Watt		950	1409	1842	2626		1194	1763	2292	3273	895	1418	2061	2598	3762	1046	1577	2275	2889	4129	1470	2174	3130	3869	5443
1400	Watt		1008	1494	1953	2786		1266	1870	2431	3471	950	1504	2186	2755	3990	1109	1672	2412	3064	4379		2306	3320	4104	5772
1600	Watt		1152	1708	2232	3183		1447	2137	2778	3967	1085	1719	2499	3149	4560	1268	1911	2757	3501	5004		2635	3794	4690	6597
1800	Watt		1296	1921	2511	3581		1628	2404	3126	4463	1221	1934	2811	3542	5130	1426	2150	3102	3939	5630		2965	4269	5276	7422
2000	Watt		1440	2135	2790	3979		1809	2671	3473	4959	1357	2149	3123	3936	5700	1585	2389	3446	4377	6255		3294	4743	5863	8246
2200	Watt		1584	2348	3069	4377		1989	2938	3820	5455	1492	2363	3435	4329	6271	1743	2628	3791	4814	6881					
2400	Watt		1728	2562	3348	4775		2170	3205	4168		1628	2578	3748	4723		1901	2866	4136	5252						
2600	Watt				3627	5173				4515			2793	4060	5116		2060	3105	4480	5690						
2800	Watt				3907	5571				4862				4372	5510				4825	6127						
3000	Watt				4186	5969				5210				4685	5904				5169	6565						
Radiatorexponent n		1,274	1,330	1,327	1,329	1,331	1,283	1,342	1,334	1,353	1,357	1,292	1,330	1,323	1,334	1,351	1,301	1,319	1,310	1,343	1,333	1,305	1,332	1,321	1,340	1,354
Type programme		COMPACT RADIATOR					T6-CENTRALLY CONNECTED RADIATOR and MULTI-FUNCTIONAL VALVE RADIATOR																			

The availability of any type of radiator, as well as range of sizes, is in accordance with the production programme, as stated in the price list.

## 32 T6-RADIATOR / MULTI-FUNCTIONAL RADIATOR / COMPACT RADIATOR

Temperature pairings 75/65/20° C and 70/55/20° C

75/65/20° C		Side panels and top cover of COMPACT-, T6- and MULTI-FUNCTIONAL VALVE RADIATORS are taken into consideration in the performance data																								
		Radiator power data in watts, in accordance with DIN EN 442 supply temperature 75 - return temperature 65 - room temperature 20° C																								
↕ Height [mm]	↔ Type	300					400					500					600					900				
		10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM
↕ Length [mm]	Power																									
400	Watt	139	226	335	438	624	178	283	419	543	774	214	337	491	617	891	250	376	543	685	981	351	517	746	918	1288
520	Watt	181	294	436	569	812	231	368	544	706	1007	279	438	638	802	1159	325	488	706	891	1276	457	672	969	1194	1675
600	Watt	209	339	503	657	937	266	425	628	814	1162	322	506	736	926	1337	375	563	814	1028	1472	527	775	1118	1378	1933
720	Watt	251	407	603	788	1124	320	510	754	977	1394	386	607	883	1111	1604	450	676	977	1233	1766	632	930	1342	1653	2319
800	Watt	278	452	670	876	1249	355	566	838	1086	1549	429	674	982	1234	1782	500	751	1086	1370	1962	702	1034	1491	1837	2577
920	Watt	320	520	771	1007	1436	408	651	963	1248	1781	493	776	1129	1420	2050	575	864	1248	1576	2257	808	1189	1715	2112	2963
1000	Watt	348	565	838	1095	1561	444	708	1047	1357	1936	536	843	1227	1543	2228	625	939	1357	1713	2453	878	1292	1864	2296	3221
1120	Watt	390	633	939	1226	1748	497	793	1173	1520	2168	600	944	1374	1728	2495	700	1052	1520	1919	2747	983	1447	2088	2572	3608
1200	Watt	418	678	1006	1314	1873	533	850	1256	1628	2323	643	1012	1472	1852	2674	750	1127	1628	2056	2944	1054	1550	2237	2755	3865
1320	Watt		746	1106	1445	2061		935	1382	1791	2556	708	1113	1620	2037	2941	825	1239	1791	2261	3238	1159	1705	2460	3031	4252
1400	Watt		791	1173	1533	2185		991	1466	1900	2710	750	1180	1718	2160	3119	875	1315	1900	2398	3434	1229	1809	2610	3214	4509
1600	Watt		904	1341	1752	2498		1133	1675	2171	3098	858	1349	1963	2469	3565	1000	1502	2171	2741	3925		2067	2982	3674	5154
1800	Watt		1017	1508	1971	2810		1274	1885	2443	3485	965	1517	2209	2777	4010	1125	1690	2443	3083	4415		2326	3355	4133	5798
2000	Watt		1130	1676	2190	3122		1416	2094	2714	3872	1072	1686	2454	3086	4456	1250	1878	2714	3426	4906		2584	3728	4592	6442
2200	Watt		1243	1844	2409	3434		1558	2303	2985	4259	1179	1855	2699	3395	4902	1375	2066	2985	3769	5397					
2400	Watt		1356	2011	2628	3746		1699	2513	3257		1286	2023	2945	3703	5347	1500	2254	3257	4111	5887					
2600	Watt				2847	4059				3528			2192	3190	4012	5793	1625	2441	3528	4454	6378					
2800	Watt				3066	4371				3800			2360	3436	4320	6238		2629	3800	4796	6868					
3000	Watt				3285	4683				4071			2529	3681	4629	6684		2817	4071	5139	7359					
Radiatorexponent n		1,274	1,330	1,327	1,329	1,331	1,283	1,342	1,334	1,353	1,357	1,292	1,330	1,323	1,334	1,351	1,301	1,319	1,310	1,343	1,333	1,305	1,332	1,321	1,340	1,354
Type programme		COMPACT RADIATOR										T6-CENTRALLY CONNECTED RADIATOR and MULTI-FUNCTIONAL VALVE RADIATOR														

The availability of any type of radiator, as well as range of sizes, is in accordance with the production programme, as stated in the price list.

70/55/20° C		Side panels and top cover of COMPACT-, T6- and MULTI-FUNCTIONAL VALVE RADIATORS are taken into consideration in the performance data																								
		Radiator power data in watts, in accordance with DIN EN 442 supply temperature 70 - return temperature 55 - room temperature 20° C																								
↕ Height [mm]	↔ Type	300					400					500					600					900				
		10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM
↕ Length [mm]	Power																									
400	Watt	113	182	270	353	503	144	228	337	436	621	174	272	396	497	716	202	303	439	551	790	284	416	602	739	1034
520	Watt	147	237	351	459	654	187	296	438	566	807	226	353	515	646	930	263	394	570	716	1027	369	541	782	960	1344
600	Watt	170	273	405	529	754	216	342	506	654	932	261	407	594	745	1073	304	455	658	826	1185	426	624	902	1108	1551
720	Watt	204	328	486	635	905	260	410	607	784	1118	313	489	713	894	1288	364	546	790	991	1422	511	749	1083	1330	1861
800	Watt	226	364	540	706	1006	288	455	674	871	1242	348	543	792	994	1431	405	606	877	1102	1580	568	832	1203	1477	2068
920	Watt	260	419	621	812	1157	332	524	775	1002	1429	400	625	911	1143	1646	465	697	1009	1267	1817	653	957	1384	1699	2378
1000	Watt	283	455	675	882	1257	360	569	843	1089	1553	434	679	990	1242	1789	506	758	1097	1377	1975	710	1041	1504	1847	2585
1120	Watt	317	510	756	988	1408	404	638	944	1220	1739	487	761	1108	1391	2003	567	849	1228	1542	2212	795	1165	1684	2068	2895
1200	Watt	340	546	811	1059	1509	433	683	1011	1307	1863	521	815	1188	1491	2147	607	909	1316	1652	2370	852	1249	1805	2216	3102
1320	Watt		601	892	1165	1660		751	1113	1438	2050	574	896	1306	1640	2361	668	1000	1448	1818	2607	938	1374	1985	2438	3412
1400	Watt		637	946	1235	1760		797	1180	1525	2174	608	951	1386	1739	2504	708	1061	1535	1928	2765	994	1457	2106	2585	3618
1600	Watt		728	1081	1412	2012		911	1349	1743	2485	695	1087	1584	1988	2862	809	1212	1755	2203	3160		1665	2406	2955	4135
1800	Watt		819	1216	1588	2263		1025	1517	1961	2795	782	1222	1781	2236	3220	911	1364	1974	2479	3555		1873	2707	3324	4652
2000	Watt		910	1351	1765	2515		1139	1686	2178	3106	869	1358	1979	2485	3578	1012	1516	2193	2754	3951		2081	3008	3693	5169
2200	Watt		1001	1486	1941	2766		1252	1854	2396	3416	956	1494	2177	2733	3935	1113	1667	2413	3030	4346					
2400	Watt		1092	1621	2118	3018		1366	2023	2614		1043	1630	2375	2981		1214	1819	2632	3305						
2600	Watt				2294	3269				2832			1766	2573	3230		1315	1970	2852	3580						
2800	Watt				2470	3521				3050				2771	3478				3071	3856						
3000	Watt				2647	3772				3268				2969	3727				3290	4131						
Radiatorexponent n		1,274	1,330	1,327	1,329	1,331	1,283	1,342	1,334	1,353	1,357	1,292	1,330	1,323	1,334	1,351	1,301	1,319	1,310	1,343	1,333	1,305	1,332	1,321	1,340	1,354
Type programme		COMPACT RADIATOR										T6-CENTRALLY CONNECTED RADIATOR and MULTI-FUNCTIONAL VALVE RADIATOR														

The availability of any type of radiator, as well as range of sizes, is in accordance with the production programme, as stated in the price list.

55/45/20° C		Side panels and top cover of COMPACT, T6- and MULTI-FUNCTIONAL VALVE RADIATORS are taken into consideration in the performance data																									
		Radiator power data in watts, in accordance with DIN EN 442 supply temperature 55 - return temperature 45 - room temperature 20° C																									
↕ Height [mm]	↔ Type	300					400					500					600					900					
		10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	
↕ Length [mm]	Power																										
400	Watt	73	115	170	222	316	92	143	212	272	387	111	171	250	312	447	129	191	278	345	497	180	262	380	463	645	
520	Watt	95	149	221	289	411	120	185	275	354	503	144	222	325	406	581	167	249	361	449	646	234	340	494	602	839	
600	Watt	109	172	255	333	475	138	214	318	408	581	166	256	375	468	670	193	287	417	518	745	271	393	570	695	968	
720	Watt	131	206	306	400	570	166	257	381	490	697	199	308	450	562	805	232	345	500	621	894	325	471	684	834	1161	
800	Watt	146	229	340	444	633	184	285	424	544	774	222	342	500	624	894	257	383	556	690	993	361	523	760	926	1290	
920	Watt	167	264	391	511	728	212	328	487	626	890	255	393	574	718	1028	296	440	639	794	1142	415	602	873	1065	1484	
1000	Watt	182	286	425	555	791	231	357	530	680	968	277	427	624	781	1117	322	479	695	863	1242	451	654	949	1158	1613	
1120	Watt	204	321	477	622	886	258	400	593	762	1084	310	479	699	874	1252	360	536	778	966	1391	505	733	1063	1297	1806	
1200	Watt	218	344	511	667	949	277	428	635	816	1161	332	513	749	937	1341	386	574	834	1035	1490	541	785	1139	1390	1935	
1320	Watt		378	562	733	1044		471	699	898	1278	366	564	824	1030	1475	425	632	917	1139	1639	595	864	1253	1529	2129	
1400	Watt		401	596	778	1107		499	741	952	1355	388	598	874	1093	1564	450	670	973	1208	1738	631	916	1329	1621	2258	
1600	Watt		458	681	889	1266		571	847	1088	1549	443	684	999	1249	1788	515	766	1112	1380	1987		1047	1519	1853	2580	
1800	Watt		516	766	1000	1424		642	953	1224	1742	499	769	1124	1405	2011	579	861	1251	1553	2235		1178	1709	2085	2903	
2000	Watt		573	851	1111	1582		713	1059	1360	1936	554	855	1249	1561	2235	643	957	1390	1725	2483		1309	1899	2316	3225	
2200	Watt		630	936	1222	1740		785	1165	1496	2129	610	940	1374	1717	2458	708	1053	1529	1898	2732						
2400	Watt		687	1021	1333	1898		856	1271	1632		665	1026	1499	1873		772	1149	1668	2070							
2600	Watt				1444	2057				1768			1111	1623	2030		836	1244	1807	2243							
2800	Watt				1555	2215				1904				1748	2186				1946	2415							
3000	Watt				1666	2373				2040				1873	2342				2085	2588							
Radiatorexponent n		1,274	1,330	1,327	1,329	1,331	1,283	1,342	1,334	1,353	1,357	1,292	1,330	1,323	1,334	1,351	1,301	1,319	1,310	1,343	1,333	1,305	1,332	1,321	1,340	1,354	
Type programme		COMPACT RADIATOR										T6-CENTRALLY CONNECTED RADIATOR and MULTI-FUNCTIONAL VALVE RADIATOR															

The availability of any type of radiator, as well as range of sizes, is in accordance with the production programme, as stated in the price list.

45/40/20° C		Side panels and top cover of COMPACT, T6- and MULTI-FUNCTIONAL VALVE RADIATORS are taken into consideration in the performance data																									
		Radiator power data in watts, in accordance with DIN EN 442 supply temperature 45 - return temperature 40 - room temperature 20° C																									
↕ Height [mm]	↔ Type	300					400					500					600					900					
		10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	10	11 K 11 KV 11 VM	21 K-S 21 KV-S 21 VM-S	22 K 22 KV 22 VM	33 K 33 KV 33 VM	
↕ Length [mm]	Power																										
400	Watt	50	78	116	152	216	64	97	144	184	262	76	117	171	213	303	88	131	191	234	339	124	178	260	315	437	
520	Watt	66	102	151	197	280	83	126	188	240	341	99	152	222	277	394	115	170	248	305	440	161	232	338	410	568	
600	Watt	76	117	174	227	324	96	145	216	276	393	115	175	256	319	455	133	196	286	352	508	186	268	390	473	655	
720	Watt	91	141	209	273	388	115	175	260	332	472	138	210	307	383	545	159	236	343	422	609	223	321	467	567	786	
800	Watt	101	156	232	303	432	128	194	289	369	524	153	233	341	425	606	177	262	381	469	677	248	357	519	630	874	
920	Watt	116	180	267	349	496	147	223	332	424	603	176	268	393	489	697	204	301	439	539	779	285	410	597	725	1005	
1000	Watt	126	195	290	379	539	159	242	361	461	655	191	291	427	532	758	221	327	477	586	846	310	446	649	788	1092	
1120	Watt	141	219	325	424	604	179	272	404	516	734	214	326	478	596	849	248	367	534	656	948	347	500	727	882	1223	
1200	Watt	151	234	349	455	647	191	291	433	553	786	229	350	512	638	909	265	393	572	703	1016	372	535	779	945	1311	
1320	Watt		258	383	500	712		320	476	608	865	252	385	563	702	1000	292	432	629	774	1117	409	589	857	1040	1442	
1400	Watt		274	407	531	755		339	505	645	917	267	408	598	745	1061	310	458	667	821	1185	434	625	909	1103	1529	
1600	Watt		313	465	606	863		388	577	737	1048	306	466	683	851	1212	354	524	763	938	1354		714	1039	1260	1748	
1800	Watt		352	523	682	971		436	649	829	1179	344	525	768	957	1364	398	589	858	1055	1523		803	1169	1418	1966	
2000	Watt		391	581	758	1079		485	722	922	1310	382	583	854	1064	1515	442	655	953	1172	1693		892	1299	1575	2184	
2200	Watt		430	639	834	1187		533	794	1014	1441	420	641	939	1170	1667	487	720	1049	1289	1862						
2400	Watt		469	697	910	1295		582	866	1106		459	700	1024	1276		531	786	1144	1407							
2600	Watt				985	1402				1198			758	1110	1383			851	1239	1524							
2800	Watt				1061	1510				1290				1195	1489				1335	1641							
3000	Watt				1137	1618				1382				1280	1595				1430	1758							
Radiatorexponent n		1,274	1,330	1,327	1,329	1,331	1,283	1,342	1,334	1,353	1,357	1,292	1,330	1,323	1,334	1,351	1,301	1,319	1,310	1,343	1,333	1,305	1,332	1,321	1,340	1,354	
Type programme		COMPACT RADIATOR										T6-CENTRALLY CONNECTED RADIATOR and MULTI-FUNCTIONAL VALVE RADIATOR															

The availability of any type of radiator, as well as range of sizes, is in accordance with the production programme, as stated in the price list.

# 34 T6-RADIATOR / MULTI-FUNCTIONAL RADIATOR / COMPACT RADIATOR

## Weights

T6 / MULTI-FUNCTIONAL						Weight in kg of T6-CENTRALLY CONNECTED and MULTI-FUNCTIONAL VALVE RADIATORS																			
↕ Height [mm]	↔ Type	300				400				500				600				900							
		11 KV 11 VM	21KV-S 21VM-S	22 KV 22 VM	33 KV 33 VM	11 KV 11 VM	21KV-S 21VM-S	22 KV 22 VM	33 KV 33 VM	11 KV 11 VM	21KV-S 21VM-S	22 KV 22 VM	33 KV 33 VM	11 KV 11 VM	21KV-S 21VM-S	22 KV 22 VM	33 KV 33 VM	11 KV 11 VM	21KV-S 21VM-S	22 KV 22 VM	33 KV 33 VM				
↕ Length [mm]	weight																								
400	kg	5,67	7,75	8,94	12,93	7,08	9,78	11,50	16,74	7,91	11,34	13,10	19,10	8,69	12,83	14,63	21,35	12,03	18,48	21,13	31,01				
520	kg	6,80	9,53	11,08	16,13	8,62	12,18	14,44	21,14	9,66	14,18	16,48	24,16	10,64	16,08	18,42	27,03	14,96	23,37	26,85	39,58				
600	kg	7,56	10,72	12,51	18,27	9,64	13,78	16,41	24,08	10,83	16,07	18,73	27,53	11,95	18,25	20,95	30,81	16,92	26,63	30,67	45,29				
720	kg	8,69	12,50	14,65	21,48	11,17	16,18	19,35	28,48	12,58	18,90	22,11	32,59	13,90	21,49	24,74	36,49	19,85	31,52	36,39	53,86				
800	kg	9,45	13,69	16,08	23,61	12,20	17,78	21,31	31,42	13,75	20,79	24,37	35,96	15,21	23,66	27,27	40,27	21,80	34,78	40,20	59,57				
920	kg	10,58	15,54	18,31	26,95	13,73	20,24	24,34	35,96	15,50	23,70	27,83	41,16	17,16	26,98	31,15	46,08	24,73	39,74	46,01	68,27				
1000	kg	11,34	16,72	19,74	29,09	14,75	21,84	26,30	38,90	16,66	25,59	30,09	44,53	18,47	29,14	33,68	49,87	26,68	43,00	49,83	73,98				
1120	kg	12,48	18,51	21,88	32,30	16,28	24,24	29,24	43,30	18,42	28,42	33,47	49,59	20,43	32,39	37,47	55,54	29,61	47,89	55,55	82,55				
1200	kg	13,23	19,69	23,31	34,44	17,31	25,84	31,21	46,24	19,58	30,32	35,72	52,96	21,73	34,56	40,00	59,33	31,56	51,15	59,37	88,26				
1320	kg	14,62	21,48	25,45	37,64	19,14	28,24	34,15	50,64	21,64	33,15	39,10	58,02	23,99	37,81	43,80	65,01	34,80	56,03	65,09	96,82				
1400	kg	15,37	22,73	26,97	39,91	20,17	29,90	36,20	53,72	22,81	35,11	41,44	61,53	25,30	40,04	46,41	68,93	36,75	59,36	68,99	102,67				
1600	kg	17,26	25,70	30,54	45,26	22,72	33,90	41,10	61,06	25,72	39,83	47,07	69,96	28,56	45,46	52,74	78,39	41,63	67,51	78,53	116,94				
1800	kg	19,16	28,84	34,30	50,84	25,28	38,07	46,20	68,64	28,64	44,73	52,90	78,63	31,82	51,04	59,25	88,09	46,51	75,83	88,26	131,46				
2000	kg	21,05	31,81	37,87	56,18	27,84	42,07	51,10	75,98	31,56	49,46	58,53	87,06	35,08	56,46	65,57	97,55	51,40	83,98	97,80					
2200	kg	22,94	34,78	41,44	61,52	30,39	46,07	56,01	83,32	34,48	54,19	64,17	95,49	38,34	61,87	71,89	107,01								
2400	kg	25,33	37,75	45,02	66,87	33,56	50,06	60,91		38,01	58,91	69,80		42,21	67,29	78,22									
2600	kg			48,59	72,21			65,82		40,93	63,64	75,43		45,47	72,70	84,54									
2800	kg			52,16	77,55			70,72			68,37	81,07			78,12	90,86									
3000	kg			55,73	82,89			75,63			73,09	86,70			83,54	97,18									
Type programme		T6-CENTRALLY CONNECTED RADIATOR and MULTI-FUNCTIONAL VALVE RADIATOR																							

The availability of any type of radiator, as well as range of sizes, is in accordance with the production programme, as stated in the price list.

COMPACT		Weight in kg of COMPACT RADIATORS																									
↕ Height [mm]	↔ Type	300					400					500					600					900					
		10	11 K	21 K-S	22 K	33 K	10	11 K	21 K-S	22 K	33 K	10	11 K	21 K-S	22 K	33 K	10	11 K	21 K-S	22 K	33 K	10	11 K	21 K-S	22 K	33 K	
↕ Length [mm]	weight																										
400	kg	3,29	4,91	6,99	8,18	12,17	4,01	6,31	9,01	10,73	15,97	4,73	7,12	10,55	12,31	18,31	5,42	7,86	12,01	13,80	20,53	7,71	11,14	17,59	20,23	30,12	
520	kg	4,00	6,05	8,78	10,33	15,38	4,93	7,84	11,41	13,67	20,37	5,88	8,87	13,38	15,69	23,37	6,77	9,82	15,26	17,60	26,20	9,74	14,07	22,48	25,96	38,69	
600	kg	4,47	6,81	9,96	11,76	17,52	5,55	8,87	13,01	15,63	23,31	6,64	10,03	15,28	17,94	26,74	7,67	11,12	17,42	20,13	29,99	11,09	16,02	25,74	29,77	44,40	
720	kg	5,18	7,94	11,75	13,90	20,72	6,47	10,40	15,40	18,58	27,71	7,78	11,79	18,11	21,32	31,80	9,02	13,08	20,67	23,92	35,66	13,12	18,95	30,63	35,50	52,96	
800	kg	5,66	8,70	12,93	15,33	22,86	7,09	11,42	17,00	20,54	30,65	8,54	12,95	20,00	23,57	35,17	9,91	14,39	22,84	26,45	39,45	14,48	20,91	33,89	39,31	58,67	
920	kg	6,37	9,83	14,78	17,56	26,20	8,02	12,96	19,47	23,57	35,19	9,68	14,70	22,90	27,04	40,36	11,26	16,34	26,15	30,33	45,26	16,51	23,83	38,84	45,12	67,37	
1000	kg	6,84	10,59	15,97	18,99	28,34	8,63	13,98	21,07	25,53	38,13	10,45	15,87	24,79	29,29	43,74	12,16	17,65	28,32	32,86	49,05	17,86	25,79	42,10	48,94	73,09	
1120	kg	7,55	11,72	17,75	21,13	31,54	9,56	15,51	23,47	28,47	42,53	11,59	17,62	27,63	32,67	48,79	13,51	19,60	31,57	36,65	54,72	19,89	28,72	46,99	54,66	81,65	
1200	kg	8,02	12,48	18,94	22,56	33,68	10,18	16,53	25,07	30,43	45,47	12,35	18,79	29,52	34,93	52,17	14,41	20,91	33,74	39,18	58,51	21,25	30,67	50,25	58,48	87,36	
1320	kg		13,86	20,72	24,70	36,89		18,37	27,47	33,38	49,87	13,67	20,85	32,36	38,31	57,22	15,94	23,17	36,98	42,97	64,18	23,46	33,90	55,14	64,20	95,93	
1400	kg		14,62	21,98	26,21	39,16		19,39	29,13	35,42	52,94	14,43	22,01	34,31	40,65	60,73	16,83	24,47	39,22	45,59	68,11	24,81	35,86	58,47	68,10	101,77	
1600	kg		16,51	24,95	29,79	44,50		21,95	33,13	40,33	60,29	16,60	24,93	39,04	46,28	69,16	19,35	27,73	44,63	51,91	77,57		40,74	66,62	77,64	116,05	
1800	kg		18,40	28,09	33,55	50,08		24,51	37,30	45,43	67,87	18,60	27,85	43,94	52,11	77,84	21,69	30,99	50,22	58,43	87,27		45,62	74,94	87,37	130,57	
2000	kg		20,30	31,06	37,12	55,43		27,06	41,30	50,33	75,21	20,51	30,77	48,67	57,74	86,27	23,93	34,26	55,63	64,75	96,73		50,50	83,09	96,91	144,84	
2200	kg		22,19	34,03	40,69	60,77		29,62	45,29	55,24	82,55	22,41	33,68	53,39	63,37	94,70	26,18	37,52	61,05	71,07	106,19						
2400	kg		24,58	37,00	44,26	66,11		32,78	49,29	60,14		24,31	37,21	58,12	69,01		28,43	41,39	66,47	77,39							
2600	kg				47,83	71,45				65,05			40,13	62,85	74,64		30,68	44,65	71,88	83,71							
2800	kg				51,41	76,80				69,95				67,57	80,28				77,30	90,04							
3000	kg				54,98	82,14				74,86					72,30	85,91				82,71	96,36						
Type programme		COMPACT RADIATOR																									

The availability of any type of radiator, as well as range of sizes, is in accordance with the production programme, as stated in the price list.