

The **FLOORTEC ECO Floor control station** consists of a complete mixing module ready for connection, which is used to regulate the flow temperature of the underfloor heating. It is suitable exclusively for connection to the **FLOORTEC stainless steel manifold**.

**Advantage:**

The **FLOORTEC ECO Floor control station** is completely pre-wired. A high-efficiency pump (power consumption 35 W) belonging to energy efficiency class A is included.



## FLOORTEC ECO FLOOR CONTROL STATION.



The **FLOORTEC ECO Floor control station** is designed for connecting an (underfloor) low-temperature heating system to an existing boiler circuit.

FLOORTEC ECO  
COMPACT CONTROL  
SYSTEM.



The **FLOORTEC ECO Compact control station** for systematic connection of small panel heating systems measuring up to approximately 25 m<sup>2</sup> consists of a mixing module (¾" Euro-Cone connection) including a shaftless spherical motor circulating pump, a built in constant temperature control system (20 – 70°C) for additional connection of a room thermostat, in order to control room temperature, and a bracket, which can be mounted on the front or on the back.



**Advantage:**

With the **FLOORTEC ECO Compact control station**, panel heaters can be connected directly to the existing radiator heating circuit.

A high-efficiency pump (power consumption 8 W) belonging to energy efficiency class A is included.